

Material Safety Data Sheet

Diesel Fuel Injector Cleaner

Official Powerplus Document 2014 Edition



Section 01: **Identification of Material and Supplier**

Product Name	Diesel Fuel Injector Cleaner
Other Names	N/A
Product Codes/Trade Names	Automotive engine additive.
Recommended Use	
Applicable In:	Australia
Supplier	Powerplus
Address	118 Swann Drive, Derrimut Victoria 3030
Telephone	+61 3 93690220
Email Address	info@acbgroup.com.au
Facsimile	+61 3 93690883
Emergency Phone Number	000 Fire Brigade and Police (Available in Australia only).
Poisons Information Centre	Poisons Information Centre: 13 11 26 (Available in Australia only).

This Material Safety Data Sheet (MSDS) is issued by the Supplier in accordance with National standards and guidelines from the Australian Safety and Compensation Council (ASCC, formerly National Occupational Health and Safety Commission - NOHSC). The information in it must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its MSDS by any other person or organization. The Supplier will issue a new MSDS when there is a change in product specifications and/or ASCC standards, codes, guidelines, or Regulations.

Section 02: **Hazard Identification**

Hazards Identification	STATEMENT OF HAZARDOUS NATURE: Classified as Hazardous according to the criteria of the Australian Safety and Compensation Council ASCC (formerly NOHSC) Approved Criteria For Classifying Hazardous Substances [NOHSC:1008] 3rd Edition. Diesel Fuel Injector Cleaner is classified as Non Dangerous good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. COMBUSTIBLE LIQUID C1, regulated under AS1940 for bulk storage purposes only.
-------------------------------	---

Risk Phrases

R38	Irritating to skin.
R65	HARMFUL- May cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.



Risk Phrases

S23	Do not breathe gas/fumes/vapour/spray.
S24	Avoid contact with skin.
S2	Avoid contact with eyes.
S36	Wear suitable protective clothing.
S37	Wear suitable gloves.
S39	Wear eye/face protection.
S51	Use only in well ventilated areas.
S09	Keep container in a well ventilated place.
S401	To clean the floor and all objects contaminated by this material, use water and detergent.
S07	Keep container tightly closed.
S13	Keep away from food, drink and animal feeding stuffs.
S26	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	If swallowed, IMMEDIATELY

Section 03: **Composition/Information on Ingredients**

Chemical Name	Synonyms	Proportion	CAS Number:
distillates (petroleum), straight- run middle, as gas oil, high flash point	-	60% w/w	64741-44-2.
Ingredients determined to be non-hazardous	-	-	Balance

Section 04: **First Aid Measures**

If poisoning occurs, contact a doctor or Poisons Information Centre.

Swallowed

If a minor amount has been accidentally swallowed, then, if conscious, rinse mouth with water and then dilute stomach contents by giving large amounts of water. Seek medical attention. Do not attempt to induce vomiting or give anything by mouth to an unconscious person. If person vomits place person on their side in recovery position.

Eyes

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.



Skin

Remove contaminated clothing. Wash contaminated skin with soap and water. Seek medical attention if swelling, redness, blistering or irritation persists. Launder contaminated clothing before re-use.

Inhaled

Remove promptly to fresh air. If there are signs of drunkenness (intoxication or inebriation) or respiratory irritation, dizziness, nausea or headache occurs, seek immediate medical attention.

Treat unconsciousness by placing the person in the coma position. Apply artificial respiration if breathing stops.

First Aid Facilities: Advice to Doctor

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.

Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.

Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.

A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

Section 05: Fire Fighting Measures

Flammability

Combustible.

Slight fire hazard when exposed to heat or flame.

Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Suitable extinguishing media

Use water spray, foam, dry chemical or carbon dioxide extinguisher or spray. Do not use water jet.

Hazards from combustion products

Burning can produce carbon monoxide and/or carbon dioxide.



Special protective precautions and equipment for fire fighters

Do not fight fire when it reached the material. Withdraw from fire and let it burn. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. First move people out of line-of-sight of the scene and away from windows.

Firefighters should wear appropriate equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

HAZCHEM Code

3Z

Section 06: Accidental Release Measures

Emergency Procedure

In the event of a major spill, clear the area of all personnel. Alert Emergency services and advise them of the nature and location of the spill. Eliminate all sources of ignition.

Wear full protective clothing and self contained breathing apparatus, especially in confined spaces. Prevent spillage from entering drains or water courses. Stop leak if safe to do so and contain spill.

Containment Procedure

Absorb using soil, sand, or other non-combustible absorbent material. Avoid using sawdust or cellulose. Sweep up and shovel or collect recoverable product into labeled containers for disposal.

Clean Up Procedure

Wash the cleaned up area with copious volumes of water to remove any trace amounts of product. Spills can be converted to non-flammable mixtures by dilution with water. Non-returnable containers should be de-gassed prior to disposal. Dispose of all waste Containers and used drums in accordance with local authority guidelines.

Section 07: Handling and Storage

Handling

Use in well ventilated areas away from all ignition sources. Intrinsically safe equipment only must be used in area where this chemical is being used.

The use of compressed air for filling, discharging, mixing or handling is prohibited due to the vapour hazard. Containers must be earthed to avoid generation of static charges when agitating or transferring product.

Observe normal hygiene standards.

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Ensure an eye bath and safety shower are available and ready for use.



Storage

Store in tightly closed containers in cool, dry, isolated and well ventilated areas away from heat, sources of ignition and incompatibles. Store away from oxidizing agents, acids, combustible materials and sources of ignition. Keep containers closed at all times – check regularly for leaks. Do not eat, drink or smoke in areas of use or storage. Observe State Regulations concerning the storage and handling of Dangerous Goods. Store with all precautions required for handling flammable liquids. The requirement of Australian Standard AS 1940 should be observed in addition to AS 1020, AS 1076, AS 2380 and AS 3000. Empty containers retain residue (liquid and/or vapour) and are dangerous. Do not pressure cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

Incompatibilities

Incompatible with the following materials:
Oxidising materials

Section 08: **Exposure Controls/Personal Protection**

Exposure Standards

National Occupational Exposure Standard (NES) Australian Safety & Compensation Council, ASCC (formerly NOHSC)
DIESEL FUEL INJECTOR CLEANER
TWA – 100mg/m³ (measured as total hydrocarbons) 8 hours, issued/revised: 1/2007 Form: Inhalable fraction and vapor.
TWA- 100mg/m³ 8 hours. Issued/Revised: 1/2007 Form: Total hydrocarbons

Notes

All occupational exposures to atmospheric contaminants should be kept to as low a level as is workable (practicable) and in all cases to below the National Standard.
These Exposure Standards are guides to be used in the control of occupational health hazards.
These Exposure Standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.
TWA (Time Weighted Average): the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.
According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.
STEL (Short Term Exposure Limit): the average airborne concentration over a 15 minute period that should not be exceeded at any time during a normal eight-hour work day.



Biological Limit Values

N/A

Ventilation

Local exhaust ventilation and/or mechanical (general) exhaust is recommended where vapours are likely to be generated. All such equipment must be intrinsically safe.

Special Consideration for Repair &/or Maintenance of Contaminated Equipment

Empty containers retain residue (liquid and/or vapour) and are dangerous. Do not pressure cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Vapour is heavier than air – prevent concentration in hollows or sumps. Do not enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Personal Hygiene Body Protection

Protective clothing (gloves, coveralls, boots, etc.) should be worn to prevent skin contact. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard “physically” away from the worker and ventilation that strategically “adds” and “removes” air in the work environment.

Skin Protection

Avoid skin contact by the use of approved chemical resistant gloves and aprons – PVC or Neoprene (AS 2161).

Eye Protection

Avoid eye contact by wearing chemical goggles with side shields or face shield (AS/NZS 1336) whenever exposed to vapour or mist or if there is a risk of splashing liquid in the eyes. Safety showers with eye-wash should be provided in all areas where product is handled. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.



[CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

Respiratory Protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Thermal Protection

None should be needed under normal circumstances.

Smoking & Other Dusts

Smoking must be prohibited in all areas where this product is used - see safety information on flammability.

Section 09: Physical and Chemical Properties

Appearance	Yellowish liquid with light petroleum odour; does not mix with water.
Odour	Petroleum odour
pH, at stated concentration	N/A
Vapour pressure	No data available
Vapour Density	No data available.
Boiling Point (°C)	No data available.
Freezing/Melting Point (°C)	No data available
Solubility	Immiscible
Specific Gravity (H₂O = 1)	0.82-0.84 at 15 °C
Flash Point	>61.5°C
Flash Point Method	No data available
Flammable (Explosive)	No data available
Limit - Upper Flammable (Explosive)	No data available
Limit - Lower Flammable (Explosive)	No data available
Auto ignition Temperature	240 °C
Evaporation Rate	No Data available
Volatile Organic Compounds Content (VOC)	(as specified by the Green Building Council of Australia) Not Applicable
% Volatiles	No data available.

Section 10: Stability and Reactivity

Stability	The product is stable
Conditions to avoid	Avoid all possible sources of ignition (spark or flame)
Incompatibility with substances/ Hazardous Reactions	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	Decomposition products may include the following materials: Carbon dioxide Carbon monoxide Other hazardous substances



Section 11: **Toxicological Information**

Toxicological Data

Health effects information is based on reported effects in use from overseas and Australian reports.

Swallowed

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.).

Eyes

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

Skin

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Irritating to skin.

Inhaled

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. may cause central nervous system depression and unconsciousness.

Effects Chronic

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

Section 12: **Ecological Information**

Eco-toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and Degradability

This product is biodegradable.



Mobility

Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments. This product is not expected to bio accumulate through food chains in the environment. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could be impaired.

Section 13: Disposal Considerations

Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material). Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14: Transport Information

Proper Shipping Name	Not regulated
UN number	Not Regulated
DG Class	Combustible liquid C1 (AS 1940)
Subsidiary Risk 1	None Allocated
Packaging Group	No data available
HAZCHEM code	3Z
Marine Pollutant	No
Special Precautions	Special Precautions for User:
Additional transport requirements	Refer to incompatibilities in section 7 and stability and reactivity information in section 10.

Section 15: Regulatory Information

Poisons Schedule

Section 16: Other Information

Contact ACB Group (ABN 79 724 186 134)
118 Swann Drive, Derrimut Victoria-3030, Australia.
Phone: +61 3 93690220
Fax: +61 3 93690883



Powerplus is a trade mark of ACB Group Pty Ltd 118 Swann Drive, Derrimut 3030 Victoria. Australia.
Ph: 03 9369 0220 Fax: 03 9369 0883 www.powerplusfuel.com.au

MSDS: COOGEE RESEARCH BLENDS. DATE ISSUED : 07 MARCH 2013

AS1020 AS1076	The Control of undesirable static electricity. Code of Practice for selection, installation and maintenance of electrical apparatus and associated equipment for use in explosive atmospheres (other than mining applications) – Parts 1 to 13.
AS/NZS 1336 AS/NZS 1715	Recommended Practices for Occupational Eye Protection Selection, Use and Maintenance of Respiratory Protective Devices
AS/NZS 1716 AS 1940	Respiratory Protective Devices The Storage and Handling of Flammable and Combustible Liquids.
AS 2161	Industrial Safety Gloves and Mittens (excluding electrical and medical gloves)
AS2380	Electrical equipment for explosive atmospheres – Explosion Protection Techniques (Parts 1 to 9).
AS3000	Electrical installations (known as the Australian/New Zealand Wiring Rules).
NOHSC:2011(2003)	National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition, April 2003, National Occupational Health and Safety Commission.
NOHSC; 2012 (1994)	National Code of Practice for the Labelling of Workplace Substances, March 1994, Australian Government Publishing Service, Canberra.
NES	National Occupational Exposure Standards for workplace Atmospheric Contaminants (NES) Australian Safety and Compensation Council, ASCC (Formerly NOHSC) 1995 as amended.
ADG Code 6th Edition	Australian Dangerous Goods Code 6th Edition
Authorisation	Reason for Issue: 5 year review Authorized by: ACB Technical Director Date of Issue: 21 September 2010 Expiry Date: September 2015

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.

