


## **Product Description**

Powerplus Diesel is suitable for all diesel-powered equipment including: High speed diesel engines, passenger cars, SUVs, trucks, agricultural, military, power generation, heating equipment, on-road, off-road and industrial applications.

## **Product Benefits**

Powerplus Diesel breaks down and removes deposits left behind on critical parts of the engine. This results in more power and increased fuel economy, whether your vehicle is old or new.



PROPERTY	UNIT	TYPICAL RESULT	TEST METHOD
Cetane Index		46 Min	ASTM D4737
Sulphur Content	PPM	10 Max	ASTM D5453
Colour	ASTM colour scale	2 Max	ASTM D1500
Appearance		Clear & Bright Pale Yellow Liquid	Visual
Density @ 15°C	kg/m3	0.82 - 0.85	ASTM D1298
Water Content	mg/kg	200 Max	ASTM D6304
Flash Point	Deg C	61.5°C Min	ASTM D93
Oxidation Stability	mg/l	25 Max	ASTM D2274

## PLEASE NOTE: Not for use in aviation applications. Do not store in fibreglass tanks or containers.

The information set out here has been compiled from standard reference materials and/or test data of Powerplus. Although Powerplus believes the information to be accurate and reliable, it is provided for the user's investigations only. Powerplus does not make or give any warranty or guarantee whatsoever. Although care has been taken in compiling the information, Powerplus hereby expressly disclaims any liability whatsoever in respect of any legligery misstatement forming part of the information.



Powerplus is a trade mark of ACB Group Pty Ltd 118 Swann Drive, Derrimut 3030 Victoria. Australia. Ph: 03 9369 0220 Fax: 03 9369 0883 **www.powerplusfuel.com.au**